

Ventilated Refrigerated GN Counter

Model	Ext. Dimension W*D*H (mm)	Int. Dimension W×D×H (mm)	Capacity (L)	Temperature (°C)	Shelf	Power Supply	Gross Weight (Kg)	Net Weight (Kg)
GN2100TN	1360×700×860	795×580×589	314	-2 ~ +8°C	2 pcs	230V/50Hz	113	98
GN2100BT	1360×700×860	795×580×589	314	$-10 \sim -20^{\circ}C$	2 pcs	230V/50Hz	118	103
GN2200TN	1360×700×960	795×580×589	314	-2 ~ +8°C	2 pcs	230V/50Hz	118	103
GN2200BT	1360×700×960	795×580×589	314	-10 ~ -20°C	2 pcs	230V/50Hz	123	108
GN3100TN	1795×700×860	1230×580×589	465	-2 ~ +8°C	3 pcs	230V/50Hz	151	134
GN3100BT	1795×700×860	1230×580×589	465	-10 ~ -20°C	3 pcs	230V/50Hz	154	136
GN3200TN	1795×700×960	1230×580×589	465	-2 ~ +8*C	3 рсв	230V/50Hz	161	139
GN3200BT	1795×700×960	1230×580×589	465	-10 ~ -20°C	3 pcs	230V/50Hz	157	139
GN4100TN	2230×700×860	1663×580×589	616	-2 ~ +8°C	4 pcs	230V/50Hz	173	153
GN4100BT	2230×700×860	1663×580×589	616	-10 ~ -20°C	4 pcs	230V/50Hz	175	155
GN4200TN	2230×700×960	1663×580×589	616	-2 ~ +8°C	4 pcs	230V/50Hz	183	158
GN4200BT	2230×700×960	1663×580×589	616	-10 ~ -20°C	4 pcs	230V/50Hz	185	160



GN2100TN / GN2100BT



GN2200TN / GN2200BT



GN4100TN / GN4100BT



GN4200TN / GN4200BT

cwsgroup.com.au